

540995

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
22 July 2004 (22.07.2004)

PCT

(10) International Publication Number
WO 2004/061981 A1

(51) International Patent Classification⁷: **H01L 33/00,**
21/20

(21) International Application Number:
PCT/JP2003/016816

(22) International Filing Date:
25 December 2003 (25.12.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
NO.2003-000442 6 January 2003 (06.01.2003) JP
60/438,997 10 January 2003 (10.01.2003) US

(71) Applicant (for all designated States except US): **SHOWA DENKO K. K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **UDAGAWA, Takashi** [JP/JP]; C/O SHOWA DENKO K.K., 1505, Shimokage-mori, Chichibu-shi, Saitama 369-1871 (JP).


(74) Agents: **AOKI, Atsushi** et al.; A. AOKI, ISHIDA & ASSOCIATES, Toranomon 37 Mori Bldg., 5-1, Toranomon 3-chome, Minato-ku, Tokyo 105-8423 (JP).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: **BORON PHOSPHIDE-BASED SEMICONDUCTOR LIGHT-EMITTING DEVICE AND PRODUCTION METHOD THEREOF**



(57) Abstract: A boron phosphide-based semiconductor light-emitting device, comprising: a crystalline substrate; a first semiconductor layer formed on said crystalline substrate, said first semiconductor layer including a light-emitting layer, serving as a base layer and having a first region and a second region different from the first region; a boron phosphide-based semiconductor amorphous layer formed on said first region of said first semiconductor layer, said boron phosphide-based semiconductor amorphous layer including a high-resistance boron phosphide-based semiconductor amorphous layer or a first boron phosphide-based semiconductor amorphous layer having a conduction type opposite to that of said first semiconductor layer; a pad electrode formed on said high-resistance or opposite conductivity-type boron phosphide-based semiconductor amorphous layer for establishing wire bonding; and a conductive boron phosphide-based crystalline layer formed on said second region of said first semiconductor layer, said conductive boron phosphide-based crystalline layer extending optionally to a

portion of said boron phosphide-based semiconductor amorphous layer, wherein said pad electrode is in contact with said boron phosphide-based semiconductor crystalline layer at a portion of said pad electrode above the bottom of said pad electrode.

WO 2004/061981 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*